

---

# Painting lead flashing

---

Lead flashing is not recommended for use with COLORBOND® prepainted steel or ZINCALUME® (aluminium/zinc/magnesium alloy-coated steel) as it can cause accelerated corrosion of the roof sheeting in some exposure conditions.

However, it is recognised that lead flashing must be retained in some re-roofing situations when lead flashing is built into the existing masonry work. In these cases, painting the underside of the lead flashing will provide a suitable barrier between the flashing and roofing sheet surfaces.

The top surface of lead flashing should also be painted with a good quality exterior paint system so that water running over the flashing is not contaminated with lead ions which may lead to contamination and corrosion of the catchment systems.

Alternatively, a plastic strip such as polythene damp course material can be used as a separator between the ZINCALUME® steel sheeting and the lead flashing. However, the top surface of the lead flashing must still be painted as a measure to help prevent contamination and corrosion of the associated catchment system. For water catchment systems supplying drinking water refer to the Australian Drinking Water Guidelines 2011 (Updated 2018) and your water testing authority for guidance.

The preferred malleable flashing material is a soft zinc sheet flashing, which is compatible with all common metallic roofing materials including zinc-coated steel, COLORBOND® steel and ZINCALUME® steel sheeting.

---

**steel.com.au**

To ensure you have the most current Technical Bulletin

**1800 800 789**

[steeldirect@bluescopesteel.com](mailto:steeldirect@bluescopesteel.com)

If you have any questions regarding this Bulletin, contact Steel Direct



---

The information and advice contained in this Technical Bulletin ('Bulletin') is of a general nature only and has not been prepared with your specific needs in mind. You should always obtain specialist advice to ensure that the materials, approach and techniques referred to in this Bulletin meet your specific requirements. BlueScope Steel Limited makes no warranty as to the accuracy, completeness or reliability of any estimates, opinions or other information contained in this Bulletin and to the maximum extent permitted by law, BlueScope Steel Limited disclaims all liability and responsibility for any loss or damage, direct or indirect, which may be suffered by any person acting in reliance on anything contained in or omitted from this Bulletin. COLORBOND®, ZINCALUME®, BlueScope and the BlueScope brand mark are registered trademarks of BlueScope Steel Limited. © 2019 BlueScope Steel Limited ABN 16 000 011 058. All rights reserved.

---